

## TECHNICAL DATA SHEET

<b>CMC TYPE</b>	<b>80725</b>
<b>Examples of application</b>	stripe-coated, impregnatable polyester fleece; popular adhesive tape for coil head tape bindings, phase separation and coil ends
<b>Supporting Base</b>	polyester fleece
Colour	white
Thickness without adhesive in mm	0.060 ± 10%
Weight without adhesive in g/m <sup>2</sup>	43 ± 10%
Total thickness in mm	ca. 0.160
Total area weight in g/m <sup>2</sup>	91 ± 10%
<b>Adhesive Properties</b>	
Type of adhesive	acrylate, stripe-coated
Adhesive strength in N/cm according to internal method PV 1006-32 (180° peel from steel)	≥ 2
<b>Thermal Properties</b>	
Temperature performance in °C	155
Short term temperature performance in °C	175
Insulation class according to IEC 60454-2	F
<b>Mechanical Properties</b>	
Tensile strength in N/cm	≥ 20
Elongation at break in %	≥ 25
<b>Other Properties</b>	
Liner	siliconized paper, yellow
Weight of liner in g/m <sup>2</sup>	ca. 90

Storage conditions: cool and dry (15 - 25°C, < 65% rel. humidity)

04/15

Quality guarantee: 12 months

The technical data are average values and subject to change without notice. They are not intended to replace user's testing.