



## Technical Data Sheet

<b>CMC TYPE</b>	<b>70752</b>
<b>Product description</b>	Double-sided adhesive tape for maximum temperature performance, also adheres to silicone surfaces.
<b>Backing material</b>	Kapton® HN (polyimide)
Colour	brown
Substrate thickness in mm	0.025 ± 17%
Total thickness in mm	0.140 ± 10%
<b>Adhesive properties</b>	
Type of adhesive	polysiloxane
Adhesive strength in N/cm according to internal method PV 1006-32 (180° peel from steel)	≥ 2
<b>Thermal properties</b>	
Temperature performance (max.) in °C	180
Short term temperature performance in °C (ca. 1 hour)	350
Insulation class according to IEC 60085	H
<b>Electrical properties</b>	
Breakdown voltage based on IEC 60243-1 in $V_{eff}$ .	ca. 7'000
<b>Mechanical properties</b>	
Tensile strength in N/cm	≥ 40
Elongation at break in %	≥ 40
<b>Other properties</b>	 
Liner	double-sided siliconized polyester
® registered trademark of DuPont de Nemours	

Storage conditions: cool and dry (15 - 25°C, &lt; 65% rel. humidity)

01/19

Quality guarantee: 12 months

The technical data are average values and subject to change without notice. They are not intended to replace user's testing.

 Note on REACH: Some of our products do contain substances from the so-called candidate list. Please visit <https://en.cmc.de/page/reach> and check whether or not a purchased product is listed in our REACH statement and therefore does contain one or more SVHCs.